

T8 & T5HO Lamps



Maximize the performance of your lighting system with high-quality T8 and T5HO lamps from **Universal Lighting Technologies**. Ideal for energy-saving retrofit projects, Universal lamps feature high color rendering for natural-looking indoor illumination, plus long lamp life with excellent lumen maintenance. Universal's high efficiency F32T8 lamps, energy saving F28T8 lamps, and high lumen T5HO lamps combine with Universal's family of energy saving ballasts such as **ULTim8®**, **DEMANDflex®**, and **AccuStart®5** for dramatic energy savings and reliable system performance.

Together, Universal lamps and ballasts enable you to meet your most demanding application requirements with components from a single source. Best of all, Universal's performance and reliability are backed up by the **System Security™** lamp and ballast system warranty.



**Lamp & Ballast
System Warranty**

	Lamp Part Number	UPC Code (768386-)	Carton Quantity
Linear T8 Lamps			
F32T8	F32T8/835A00C	25736	30
	F32T8/841A00C	25737	30
	F32T8/850A00C	25738	30
F32T8HL High Lumen	F32T8/835HLA00C	25898	30
	F32T8/841HLA00C	25899	30
	F32T8/850HLA00C	25900	30
F28T8	F28T8/835A00C	25877	30
	F28T8/841A00C	25878	30
	F28T8/850A00C	25879	30
F25T8 (3 FT.)	F25T8/835A00C	25874	30
	F25T8/841A00C	25875	30
F17T8 (2 FT.)	F17T8/835A00C	25873	30
	F17T8/841A00C	25871	30
U-Bend T8 Lamps			
F32T8 U-Bend 6" Leg	FB32T8/835/6A00C	25865	10
	FB32T8/841/6A00C	25866	10
T5HO Lamps			
F54T5HO	F54T5HO/835B00C	27422	40
	F54T5HO/841B00C	24987	40
	F54T5HO/850B00C	24991	40

Linear T8 Lamps	Lamp Part Number	Lamp Watts	Lamp Life** (Hours)	Approx. Lumens		CCT (°K)	CRI	Length
				Initial	Mean			
F32T8	F32T8/835	32	24000	2950	2800	3500	84	48
	F32T8/841	32	24000	2950	2800	4100	84	48
	F32T8/850	32	24000	2800	2660	5000	82	48
F32T8 High Lumen	F32T8/835HL	32	24000	3100	2915	3500	84	48
	F32T8/841HL	32	24000	3100	2915	4100	84	48
	F32T8/850HL	32	24000	3000	2820	5000	82	48
F28T8	F28T8/835	28	24000	2725	2590	3500	84	48
	F28T8/841	28	24000	2725	2590	4100	84	48
	F28T8/850	28	24000	2600	2470	5000	82	48
F25T8 (3 FT.)	F25T8/835	25	24000	2225	2050	3500	84	36
	F25T8/841	25	24000	2225	2050	4100	84	36
F17T8 (2 FT.)	F17T8/835	17	24000	1325	1200	3500	84	24
	F17T8/841	17	24000	1325	1200	4100	84	24
U-Bend T8 Lamps								
F32T8 U-Bend 6" Leg	FB32T8/835/6	32	24000	2850	2620	3500	84	22.5
	FB32T8/841/6	32	24000	2850	2620	4100	84	22.5
T5HO Lamps								
F54T5HO*	F54T5HO/835	54	25000	5000	4600	3500	85	48
	F54T5HO/841	54	25000	5000	4600	4100	85	48
	F54T5HO/850	54	25000	4900	4508	5000	85	48

* T5HO data is for 35°C Operation

Specifications Subject to Change Without Notice

** Lamp life rating based on 3 hours per start (T8 - Instant Start, T5HO - Programmed Start)

LIT# T8T5HO0510

www.unvlt.com

Universal Lighting Technologies is a subsidiary of Panasonic Electric Works Co., Ltd., a member of the Panasonic Group

Panasonic

Universal
Lighting Technologies